
Offset Printing


## Print & Artwork Guidelines

A guide to our three printing methods, and how to achieve the best results.



## Contents

This document will provide an overview of all three print methods, including the artwork guidelines for each of them.



## **CMYK Digital Printing**

Quantity range	1–2000 units
Set-up costs?	No
Lead times	Est. 8 days*

③ Most popular

Used for online orders

#### $\bigcirc$ What is CMYK Digital Printing?

Digital printing is the process of printing digital-based images directly onto the cardboard surface, using a CMYK colour model. With a high-quality finish, short turnaround time and no set-up fees, it is the most popular choice for the majority of customers. CMYK stands for the four primary colours used for Digital Printing – Cyan, Magenta, Yellow and Key (Black).





#### $\bigcirc$ Benefits of CMYK Digital Printing

- No minimum order quantity
- No set-up costs
- High quality finish
- Waste-preventative
- Fast turn–around time

#### How to check if your document is set up in CMYK:

- Photoshop: *Properties > Mode > CMYK*
- Illustrator: *File > Document Colour Mode > CMYK*

\*Lead times are based on estimates only.





## **Digital Printing Guidelines**

Please make sure your design meets our printing requirements.

Feel free to use this as a checklist for your artwork!

Aa	<b>Text</b> Keep text to a min. of 12pt or higher for best results. We recommend fonts with thin strokes to be higher than 14pt.		<b>PANTONE</b> 7479 C	Pantone colours Please set all Pantone colours to the nearest CMYK equivalent to accommodate for digital production.
	Full-colour print Your design can use any CMYK colour, all without affecting the total cost! The bolder your colours, the better the results.		20.20.20.100	Black settings Please set all rich black elements to CMYK: 20% 20% 20% 100%. We suggest printing black designs in matte and on white stock.
	<b>Graphics</b> We prefer vector over raster graphics where possible. Use photography at 300dpi or higher.		Shift + Command + O	Convert text to outlines All text must be converted to outlines or have the font supplied with the artwork file (.otf or .ttf).
$\downarrow \downarrow$	Embed all files Please make sure that all images are embedded instead of being linked within your file.			Template Do not change or re-size the lines of the template. Artwork with a modified template means your box will not function correctly.
	Lines Please ensure all lines used in your design are at least 0.5mm wide.			Important elements Keep important elements of your design at least 5mm away from cut lines and side edges.
arc abras	Kraft packaging* Do not print white ink to Kraft surfaces, all white in your design will be left unprinted. *Please get in touch if you want white ink on	C) Kraft.		Australian–Made badge Add our Eco badge to your design to show your commitment to sustainable and Australian–Made packaging!

## **Offset Printing**

Pantone colour compatible

Also known as lithographic printing

Quantity range	2000+ units*	
Set-up costs?	Yes	
Lead times	Est. 2–3 weeks*	

#### $\bigcirc$ What is Offset Printing?

Lithographic (or 'offset') printing is a method ideal for printing photography, fine detail, gradients and vibrant colors. It produces a very high-quality print on paper with highly-detailed and smooth images, which is then mounted onto cardboard, giving it a seamless finish.

\*Lead times are based on estimates only. Please contact our team for more info.

# HIGHEST QUALITY

#### $\ominus$ Benefits of Offset Printing

- Highly detailed, flat and sharp images
- High quality paper stock
- Can use any combination of CMYK or PMS colours, including metallic inks
- Solid PMS Pantone colour (a.k.a., it looks perfect)

**Note:** There may be a one-time set up cost for your first order, and then you only pay for the unit cost for future orders.





### **Offset Printing Guidelines**

Please make sure your design meets our printing requirements.

Feel free to use this as a checklist for your artwork!

Aa	Text Use a min. of 4pt for best results, or min. of 6pt for thin-stroke fonts. Reversed out fonts should be 2pt higher than the above.	<b>PANTONE</b> 7479 C	Pantone colours
	Full-colour print         Your design can use any CMYK         colour, all without affecting the total         cost! The bolder your colours, the         better the results.	0.0.0.100	Black settings
	Graphics and files Use vector over raster graphics where possible and photography at min. 300dpi. Please embed all images.	Shift + Command + O	Convert text to outlines
*	Special finishes Other special finishes may be available at additional cost. Consult your representative for more information.		Template  Do not change or re-size the  lines of the template. Artwork with  a modified template means your  box will not function correctly.
	Lines Please ensure all lines used in your design are at least 0.1mm wide.		Important elements
(MAR)	Kraft packaging White can be printed onto Kraft — other light colours will appear washed out and muddy. Darker colours will appear better.		Australian-Made badge Add our Eco badge to your design to show your commitment to sustainable and Australian-Made packaging!

## **Flexographic Printing**

Quantity range	2000+ units*	
Set-up costs?	Yes	
Lead times	Est. 2–3 weeks*	

#### $\bigcirc$ What is Flexographic Printing?

**'Flexo'** is often the most budget-friendly option available in volume. It is best for printing designs that don't have small text, fine details, or photos. Some colour and coverage variation can occur between units in the same order. You can see the comparison between Digital Printing and Flexo Printing below.

\*Lead times are based on estimates only. Please contact our team for more info.





#### ⇒ Benefits of Flexographic Printing

- Highly affordable unit cost
- Biodegradable print method
- Uses water-based inks
- Pantone colour compatible

**Note:** There may be a one-time set up cost for your first order, and then you only pay for the unit cost for future orders.



**Digital Printing** 



**Flexographic Printing** 

## **Flexo Printing Guidelines**

Please make sure your design meets our printing requirements.

2pt higher than the above.

Print colours

Text

Feel free to use this as a checklist for your artwork! Pantone colours Use a min. of 12pt (min. 14pt Use Pantone colours if possible, for thin-stroke / serif fonts). as PMS-xxxU. See Flexo standard Reversed out fonts should be colour chart for a list of standard PANTONE 7479 C available colours. Other colours available on request. Variation in production Max. 2 colours for best results Colour may vary due to water- $\downarrow$ (more colours are possible but may based inks. We recommend cause issues). Dark colours print Pantone spot colours. Avoid best. Do not join/overlay colours. designing over crease lines. Convert text to outlines All text must be converted Shift + to outlines or have the font Command + O supplied with the artwork file (.otf or .ttf). Template Must be checked by the client / Do not change or re-size the issuer. Must be in a dark colour lines of the template. Artwork with and bars must be parallel to the a modified template means your box will not function correctly. Important elements Keep min. 10mm away from cut lines / edges. Allow 3mm for print colour overlap and movement, and 7mm for cutting movement.



#### Kraft packaging

Ensure all lines are at least

1mm wide. Reversed-out

lines should be a minimum

White can be printed onto kraft - other light colours will appear washed out and muddy. Darker colours will appear better.



#### Australian-Made badge

Add our Eco badge to your design to show your commitment to sustainable and Australian-Made packaging!

		m	*
×c	M	3	4

#### Graphics and files

Barcodes

flute direction.

Lines

of 1.5mm.

All files must be provided in a vector format. Photography cannot be easily printed, so we strongly discourage its use.





We've made it easy to connect with designers. Read our blog on how you can find a freelance designer.



For any other questions, feel free to reach out at hello@inke.com.au